

HHP - HOLE PUNCHERS




Punching force up to 50 tonnes

Throat depth 70mm

Working pressure 700 Bar

The Hi-Force HHP series hydraulic hole puncher range offers a choice of two models comprising of the HHP30, 30 tonnes capacity single acting version, and the HHP50, 50 tonnes capacity double acting version. Both models are suitable for punching holes in steel plate as per the respective capacity of each model and are supplied complete with standard punch and die sets and an integral positioning and carrying handle. See pages 29-50 for detailed information of suitable pumps for use with HHP series punchers.





Model	Maximum force	Throat depth	Steel	capacity (mm) Hole punch	Standard punch/die sets included	Manually	d pump & hose Pneumatically	
number	tonnes	mm	plate	diameter	mm	operated	operated	kg
ннрзо	30	70	10.0	up to 20.5	10.5, 13.5 17.5, 20.5	HP232 complete with HC3 3m hose	AHP1120 complete with HC3 3m hose	13
ННР50	50	70	15.0	up to 25.5	10.5, 13.5 17.5, 20.5, 25.5	HP232D c/w 2 x HC3	AHP1141 c/w2xHC3	42

Note: pump supplied separately

Model	Dimensions in mm							
number	А	В	С	D				
HHP30	370.0	220	13	78.0				
HHP50	413.5	281	15	70.6				



The HHP30 is single acting operation, the HHP50 is double acting operation